

Re: EBCDIC to ASCII OPTCD=Q? (JCL)

Source: <http://coding.derkeiler.com/Archive/Cobol/comp.lang.cobol/2006-09/msg00331.html>

- *From:* Howard Brazee <howard@xxxxxxxxxx>
 - *Date:* Thu, 21 Sep 2006 09:59:39 -0600
-

On Thu, 21 Sep 2006 13:59:44 +0000 (UTC), docdwarf@xxxxxxxxxx () wrote:

... to create an &&TEMP with X'40' EBC in the right place which is then used as input instead of NODE1.NODE2.EBCDIC.DATA.

Passing on another tidbit:
Howard,

If you're just trying to change the 19,16 field, you could use DFSORT's OVERLAY function to simplify your OUTFIL statement:

```
OUTFIL FNAMES=SORTOUT,  
OVERLAY=(19:19,16,TRAN=ALTSEQ)
```

Frank Yaeger – DFSORT Team (IBM)
Specialties: PARSE, JFY, SQZ, ICETOOL, IFTHEN, OVERLAY, Symbols,
Migration

=> DFSORT/MVS is on the Web at <http://www.ibm.com/storage/dfsort/>

For IBM–MAIN subscribe / signoff / archive access instructions,
send email to listserv@xxxxxxxxxx with the message: GET IBM–MAIN INFO
Search the archives at <http://bama.ua.edu/archives/ibm-main.html>