

# Re: simple CLI architecture

---

*Source:* <http://coding.derkeiler.com/Archive/General/comp.arch.embedded/2005-06/msg00250.html>

---

- *From:* "Roman Mashak" <[mriv@xxxxxxxx](mailto:mriv@xxxxxxxx)>
  - *Date:* Wed, 8 Jun 2005 11:55:04 +0900
- 

Hello, Scott!

You wrote on Fri, 03 Jun 2005 11:52:04 -0700:

??>> command 2) parse command line 3) execute code related to command Seems  
??>> to be simple but I don't have any idea right now, that's why I ask for  
??>> you to help me out :) With best regards, Roman Mashak. E-mail:  
??>> [mriv@xxxxxxxx](mailto:mriv@xxxxxxxx)

SM> Do yourself and all your users a big favor. Use a predefined CLI  
SM> package. My favorite is embedded TCL.  
What do you think about using flex+bison for my task? The only reason  
that stops me is I don't know this well.

With best regards, Roman Mashak. E-mail: [mriv@xxxxxxxx](mailto:mriv@xxxxxxxx)

.

---

• *References:*

- ◆ [\*simple CLI architecture\*](#)
  - ◇ *From:* Roman Mashak
- ◆ [\*Re: simple CLI architecture\*](#)
  - ◇ *From:* Scott Moore
- Prev by Date: [\*Re: Minimum PIC18F4431/ICD2 arrangement\*](#)
- Next by Date: [\*Re: keypad scanner\*](#)
- Previous by thread: [\*Re: simple CLI architecture\*](#)
- Next by thread: [\*read IDE HD physical 0 sector\*](#)
- Index(es):
  - ◆ [\*Date\*](#)
  - ◆ [\*Thread\*](#)