

Re: Send out different content depends on User Agent String

Source: <http://coding.derkeiler.com/Archive/PHP/comp.lang.php/2006-01/msg02067.html>

- *From:* "NC" <nc@xxxxxxxx>
 - *Date:* 27 Jan 2006 08:07:28 -0800
-

Allerdyce.John@xxxxxxxx wrote:

- >
- > Is there an easy way in PHP which send outs different content
- > depends on User Agent String value?

Yes. There is a superglobal variable `$_SERVER['HTTP_USER_AGENT']`

- > If yes, is there an example/documentation?

Here is the documentation on the subject in its entirety:

'HTTP_USER_AGENT'

Contents of the User-Agent: header from the current request, if there is one. This is a string denoting the user agent being which is accessing the page. A typical example is: Mozilla/4.5 [en] (X11; U; Linux 2.2.9 i586). Among other things, you can use this value with `get_browser()` to tailor your page's output to the capabilities of the user agent.

Source:

<http://www.php.net/manual/en/reserved.variables.php#reserved.variables.server>

Cheers,
NC

• *References:*

- ◆ [*Send out different content depends on User Agent String*](#)
 - ◇ *From:* Allerdyce . John
- Prev by Date: [*Re: Is W32api dead?*](#)
- Next by Date: [*Re: PHP-Yes, HTML-No --- Why?*](#)
- Previous by thread: [*Re: Send out different content depends on User Agent String*](#)
- Next by thread: [*Re: Send out different content depends on User Agent String*](#)

Re: Send out different content depends on User Agent String

- Index(es):

- ◆ *Date*

- ◆ *Thread*